


ATMOSPHERE PHOENIX

PRODUCT SPECIFICATIONS



TO MARKET

SIZE	Straight Edge Tile: 38" x 38" Interlocking Tile: 37" x 37"
THICKNESS	Through-Body Color Tiles: 4, 6, 8 and 10mm Strata Tiles: 7, 8, 10 or 12mm
COMPOSITION	Varies per product and construction Styrene Butadlene Rubber (Granulated SBR) is 100% post-consumer recycled tires Elthylene-Propylene Diene Monomer (Colored Grains of EPDM) contain varying levels of pre-consumer recycled content
FLOORSCORE®	Certified SCS-FS-02937
ABRASION & WEAR RESISTANCE	ASTM-C501 0.502 grams / 1000 cycles ± 5mg
DENSITY (PCF)	ASTM-D3676 66 lbs. /cu. ft.
SHORE HARDNESS	ASTM-D2240 65
STATIC LOAD LIMIT	ASTM-F970-87 0.0% residual compression (standard test method for static load limits - 250 lbs. / sq. inch loading)
COMPRESSION	ASTM-D395 9.7%
CRITICAL RADIANT FLUX	ASTM-E-648-94A - Class I / Class II (complete details available upon request)(Port Authority of NY and NJ) See your To Market Sales Representative for details
INDOOR AIR QUALITY	Product passes VOC Emissions - Washington State / FloorScore® certified Adhesive used with straight edge mat format, Chemrex CX-941, complies with SCAQMD Rule #1168 as required by LEED®. MSDS available upon request.
ACOUSTIC RATING	Superior ASTM-E989-06/E492-96 4mm 11C 57 / 8mm 11C 59 (Impact Sound Transmission/Impact Insulation Class - tested on concrete with plenum)
ELONGATION AT BREAK	ASTM-D412 120%
TENSILE STRENGTH	ASTM-D412 290.2 lbs. / square inch
COEFFICIENT OF FRICTION	ASTM-D2047-93 1.04 Dry 1.05 Wet (James test method) Exceeds ADA recommended of .60 for flat surfaces/.80 for ramps
ACCELERATED FLOOR TRAFFICKING	5 – no change in performance
CHEMICAL/STAIN RESISTANCE	ASTM-F 925 No change (ammonia, bleach, rust, grass, coffee, fruit juice, cola, ink, lipstick)
CUSTOM	Custom colors, logo or graphic designs available.
WARRANTY	10-year limited commercial warranty. See tomkt.com for complete details.
COUNTRY OF MANUFACTURER	Canada