


# OZOGrip GALLERY

## PRODUCT SPECIFICATIONS



TO MARKET

STYLE NAME	Ozogrip® Gallery Collection Whitney, MoMa and Tate
SIZE	Whitney 12" x 24" tiles 10 tiles/carton 2 s/f per tile 20 s/f carton  MoMa: 12" x 24" tiles 10 tiles/carton 2 s/f per tile 20 s/f carton  Tate: 7.08" x 47.24" planks 10 planks/carton 2.32 s/f per plank 23.2 s/f carton  Tate TM 412 only: 9.25" x 59.25" planks 8 planks/ carton 3.81 s/f per plank 30.45 s/f carton
GAUGE	5.0mm
WEAR LAYER	.5mm (20 mil)
FINISH	Ozocoat+ Technology (Added for anti-microbial, anti-fungal and anti-bacterial protection)
FLOORSCORE®	Certified SCS-FS-03764
INDOOR AIR QUALITY	SCS-EC10.3-2014
COEFFICIENT OF FRICTION	ASTM D2047 (James Method) Exceeds ADA Requirements
REFERENCED SPECIFICATIONS	ASTM F-1700, Class III, Type B, Embossed Surface (Meets or exceeds requirements for composition, size, thickness, squareness, flexibility, dimensional stability, and resistance to chemicals)
CRITICAL RADIANT FLUX	ASTM E648-08 Class I – 1.06 watts cm <sup>2</sup>
FLEXIBILITY	ASTM F-137-08 Passes 6mm Mandrel
STATIC LOAD LIMIT	ASTM F970-07 Passes 1,000 PSI Modified
MAINTENANCE	Requires no wax, no stripping, no buffing or toxic seal coat
WARRANTY	15-Year commercial warranty
RESISTANCE TO CHEMICALS	ASTM F925-02 No surface dulling, surface attack, color change (5 acetic acid, 70% Isopropyl alcohol, mineral oil, 5% sodium hydroxide, 5% Hydrochloric acid 5% ammonia, bleach, 5% phenol, gasoline, sulfuric acid, Kerosene, and olive oil)
MOISTURE MAXIMUMS	Up to 8lbs — Calcium Chloride or Hydrostatic Pressure — PH no greater than 11— RH no greater than 85%