



Description:	No wax, No buff, Scuff resistant - Commercial resilient sheet vinyl	
Dimensions:	6' wide x 65.6' long rolls / 43.77 square yards per roll	
Overall Gauge:	2.2mm (0.87")	
Weight:	5.7 pounds per square yard	
Wear Layer:	Type 1– Grade 1 per ASTM F1303 - embossed anti-microbial clear polyurethane 20mil wear layer	
Coating:	High Definition - OzoCoat+ Technology for superior stain resistance which provides anti-bacterial, anti-fungal, and anti-static protection	
Characteristics:	Classification ASTM F1303	
Backing Class:	Class B: 4-ply fused backing system of 0.87 in PVC wear layer, Printing layer, Fiberglass layer for extra dimensional stability, and PVC backing layer recycled	
Critical Radiant Flux:	ASTM-E648	>.45 watts /m ² - Class 1
Smoke Density:	ASTM-E662	<450 in flaming mode
Static Load Limit:	ASTM-F970	Rated at 1,300 PSI Modified
Wear Resistance:	ASTM-4060 Passes	
Flexibility:	ASTM-F137 Passes	
Slip Resistance:	ASTM-D2047 Meets and Exceeds Requirements	
Resistance/Chemicals:	ASTM-F925-02 Passes	
Antimicrobial Activity:	ISO-22196 – 1.9 x 10 ⁴ CFU (Colony Forming Unit) after 24 hours Blank 2.3 x 10 ⁴ – OzoTEC <10	
Resistance to Fungi:	ASTM-G21 – Grade 0 – observed no growth on sample	
Recycled Content:	67% total recycled content 30.2% Pre-Consumer / 36.8% Post-Consumer	
Air Quality:	No buffing means better air quality – Non Toxic G88+ Technology No wax particles vaporized into the air No bacterial particles or toxins into the air No dust particles dispersed into the air No irritating odors from floor finish and strippers	
Pattern Repeat:	36" x 59"	
FloorScore:	SCS Certified – SCS-FS-03353	
Wear Warranty:	15-Year Limited Commercial Warranty	