URBAN 20

PRODUCT SPECIFICATIONS

Style Name Urban 20

Pattern Names Granite | Ironstone | Plank | Metallo

Composition Phthalate Free Virgin Vinyl

Gauge 3mm Wear Layer 20 mil

Finish Advanced Ceramic Bead Barrier + Coating - No Wax, No Buff

Standard Size Granite 12" x 24" tiles

Ironstone 6" x 36" planks Plank 4" x 36" planks Metallo 12" x 24" tiles

Custom Options: Granite - No custom sizes

Ironstone 7.25"x48" – 2,126 s/f minimum Plank 6"x36" for a 1,620 s/f minimum OR Plank 7.25"x48" for a 2,126 s/f minimum

Metallo - No custom sizes

Pieces per carton Granite – 18 tiles per carton

Ironstone – 36 planks per box Plank - 36 planks per box Metallo – 18 tiles per carton

Square Feet per carton: 36

Coefficient of Friction ASTM D-2047 (James Machine) >.6

Meets + Exceeds Requirements

Dynamic Coefficient

of Friction ANSI B101.3 Meets + Exceeds Requirements

Critical Radiant Flux ASTM E-648 Class 1 Meets + Exceeds Requirements

Smoke Density ASTM E-662 (Flaming /Non-Flaming) <450

Exceeds Requirements

Static Load Limit ASTM F-970 – Passes - 1,500 PSI Modified

Reference Specifications ASTM F-1700 Solid Vinyl Floor Tile and Plank

Class III, Type B – Embossed Surface Meets + Exceeds Passing Requirements

Resistance to Chemicals ASTM F-925 Passes / No Change

White vinegar, Rubbing alcohol, White Mineral Oil, Sodium Hydroxide

Solution, Hydrochloric Acid Solution, Sulfuric Acid Solution,

Household Bleach Solution, Olive Oil, Kerosene, Unleaded Gasoline,

Phenol

FloorScore®: SCS-FS-03973

Warranty: 10-Year Limited Commercial Warraty

Country of Manufacture China

TO MARKET GLOBAL 866.772.4772 tomkt.com ©2018 To Market Global

TO MARKET